



# TECTORIUS™ TEC-EIZE™

Thread Lubricant and Anti-Seize Compound

## DESCRIPTION:

Tec-Eize thread lubricants and anti-seize compounds are a group of materials specially designed for fasteners and components to reduce friction, increase job efficiency, and facilitate installation and removal processes over extended periods.

This product family is intended for mass pre-application onto fasteners, fittings and components—in situations where automated installation will occur later, and on-site use of materials is not possible or ideal.

## APPLICATIONS:

- » Tri-lobular thread forming bolts
- » Thread cutting fasteners of all types
- » Springs and spring clips
- » Gall susceptible substrates (i.e. aluminum and stainless steel)
- » Seat and window guides
- » Many more

## PRODUCT FEATURES:

- » Reduces effort required for installation of fasteners and additional components by as much as 75%.
- » Reduces surface wear.
- » Squeak and rattle reduction.
- » Eliminates galling and installation torque 'chatter'.
- » Available in several grades with varying degrees of lubrication, color, and application methods.



# TECTORIUS™ TEC-EIZE™

Thread Lubricant and Anti-Seize Compound

## SPECIFICATIONS:

Grade:	95CT	630	631	632
Color	White	Black	Bronze	Black
Primary Usage	High Performance	Anti-Seize/ High Temp.	Anti-Seize/ High Temp.	Anti-Seize/ Specialty
Application Method	Flow	Flow	Flow	Flow
Typical Use	Metal Forming	Serviceable Parts	Serviceable/ High Wear Parts	Serviceable/ Specialty
Temperature Range	Up to 225° F	Up to 1200° F	Up to 1200° F	Up to 1500° F
Lubricity	Very High	Medium	Medium	Medium
On-Part Life*	Indefinite	Indefinite	Indefinite	Indefinite

\* Varies due to storage conditions.

Note: If you don't see the product you are looking for, ask us about our **Tec-Slip™ dry film lubricant** coatings and other lubricating product lines. These may also be effective for your specific application.