



DESCRIPTION:

Squeak-Stop is a universal lubricant for eliminating squeaks, rattles, associated noises and wear. This ‘anti-squeak’ all-purpose formula is a blend of high and low molecular weight hydrocarbons, waxes, and mineral oils. It is used to eliminate noise on many surfaces including vinyl, metal, glass, and an assortment of plastics. The product is effective across a wide range of temperatures.



METHOD OF USE:

Squeak-Stop is applied as a thin film between two contacting surfaces to prevent squeaks in interiors of automobiles. It is easily applied with a cloth, sponge, or brush. The recommended application rate is 15mg of the compound per square inch of contacting surface. Any excess amounts of the material should be removed with a clean, dry cloth.

PRODUCT FEATURES:

- » **Durable:** This time and money saving product allows for easy application of a long-lasting and durable lubricant.
- » **Simple:** Squeak-Stop is an easy-to-apply general purpose lubricant leaving no drips, no stains, and no harsh odor.
- » **Versatile:** Can be used on a variety of many plastics (polypropylene, polyethylene, nylon, polyester, and acetal).
- » **Environmentally friendly:** A non-toxic, non-corrosive, non-staining formula that can be washed away with soap and water.
- » **Unlimited shelf life:** This product can be stored indefinitely without losing effectiveness.



SPECIFICATIONS:

Available Size	1.75 oz. tin
Appearance	Typically a soft, neutral paste
Odor	Pleasant, nontoxic
Melt point	120° F
Specific Gravity	0.89 (70° F)