

## LOXEAL 08-07

### Description

Tixotropic permanent plastic sealant for use on threaded and flanged joints.  
Do not harden and joints can be easily dismantled.  
Seals against gas, LPG, water, gasoline, oils.  
Can be used in combination with preformed gaskets or alone for gap joints less than 0,1 mm.  
Resistant to vibrations, thermal shocks, keeps sealing properties within a temperature range of -50 / + 120°C.  
Prevents from surfaces corrosion.  
Approved by Volkswagen for use in motor parts assembly (Ref. AKD 454300).

### Physical properties

* Composition:	polyester resin
* Colour:	blue
* Viscosity (25°C - Pa.s):	1.000M – 6.000M
* Specific weight (g/ml):	1,1
* Fluorence:	under blue light
* Flash point:	> 200°C
* Shelf life 25°C:	1 year minimum
*Temperature range:	-55 +120°C

### Directions for use

Clean and degrease surfaces with Loxeal Cleaner 10. Apply the product in quantities sufficient to fill the joints completely. The sealant provides instant sealing and assembled pieces can be used and tested immediately

### Storage

Keep product in a cool and dry room at +25°C. To avoid contaminations do not refill containers with used product. For more information on applications, storage and handling contact Loxeal Technical Service

### Safety and handling

Consult Material Safety Data Sheet

### Note

The data contained herein, obtained in Loxeal laboratories, are given for information only. Loxeal cannot assume responsibility for the results obtained by others which methods are not under Loxeal control. It is the user's responsibility to determine suitability for the user's purpose of any product mentioned herein. Loxeal disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Loxeal products. Loxeal specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.