

Preliminary

Loxeal CR 5 Gel

Description

Loxeal CR5 Gel is a high viscosity, low odor and low volatility solvent to be used to detach and remove silicones, Ms Polymers and two-part modified epoxy adhesives from many kinds of surfaces.

Physical properties

Appearance: transparent / opaque

Viscosity: gel

Shelf life: 12 months at +5°C/+25°C in unopened packaging

Directions for use

Apply CR5 Gel on a cured sealant; removing time may vary from several minutes to several hours, depending on the sealant's thickness.

Recommendation

The solvent may deteriorate and damage some plastics, covering and fabrics. We suggest checking compatibility of the product with all the surfaces before applying it.

Storage

Keep product in a cool and dry room at a temperature between +5°C and +25°C. To avoid contaminations do not refill containers with used product. For further information on applications, storage and handling contact Loxeal Technical Service

Safety and handling

Consult Material Safety Data Sheet before use.

Note

The data contained herein, obtained in Loxeal laboratories, are given for information only; if specifics are required, please contact Loxeal Technical Department. Loxeal ensures abiding quality of supplied products according to its own specifics. Loxeal cannot assume responsibility for the results obtained by others which methods are not under Loxeal control. It is user's responsibility to determine suitability for user's purpose of any product mentioned herein. Loxeal disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Loxeal products. Loxeal specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.