

# Technical Data Sheet

Preliminary

## Loxéal CR 5

### Description

Loxéal CR5 is a low odor and low volatility solvent to be used to detach and remove silicones, Ms Polymers and two-part modified epoxy adhesives from many kinds of surfaces.

### Physical properties

Appearance:	transparent
Viscosity:	liquid
Shelf life:	12 months at +5°C/+25°C in unopened packaging

### Directions for use

Apply CR5 Gel on a cured sealant; removing time may vary from several minutes to several hours, depending on the sealant's thickness.

### Recommendation

The solvent may deteriorate and damage some plastics, covering and fabrics. We suggest checking compatibility of the product with all the surfaces before applying it.

### Storage

Keep product in a cool and dry room at a temperature between +5°C and +25°C. To avoid contaminations do not refill containers with used product. For further information on applications, storage and handling contact Loxéal Technical Service

### Safety and handling

Consult Material Safety Data Sheet before use.

### Note

The data contained herein, obtained in Loxéal laboratories, are given for information only; if specifics are required, please contact Loxéal Technical Department. Loxéal ensures abiding quality of supplied products according to its own specifics. Loxéal cannot assume responsibility for the results obtained by others which methods are not under Loxéal control. It is user's responsibility to determine suitability for user's purpose of any product mentioned herein. Loxéal disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Loxéal products. Loxéal specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.