

# Technical Data Sheet Silicone oil pure type 12500

# Description

High viscosity Silicone oil type 12500 is an anti adhesive and lubricant to metals, plastic parts and rubbers.

Composition :	polysiloxane based
Viscosity at +25°C :	12500
Viscosity at -20°C :	37000
Viscosity at +150°C :	1800
Specific weight at +25°C :	0,97 g/ml
Temperatura solidificazione :	-50°C
Flash point :	above +300°C
Tensione superficiale :	21 dyne/cm

#### **Physical Properties**

Silicone oil type 1000 is insoluble in water, mineral oils, acid solutions and bates, salt solutions; it could be removed by organic solvents.

#### **Chemical Resistance**

Silicone oil type 1000 is chemically inactive; it could be attacked by strong oxidizing agents (nitric acid, peroxide, dichromate and permanganate) in prolonged direct contact.

## Toxicity

Silicone oil type 1000 doesn't contain any hazard substance or dangerous one (non-toxic like).

It can be used in environments in contact with drinking water or food areas.

#### Antiadhesion

Silicone oil type 1000 is an anti adhesion product; it could be avoided any contamination with metal parts that undergo painting, surface treatments or electroplating bath.

# Storage

Keep product in a cool and dry room at temperature of +5/ +25°C. To avoid contaminations do not refill containers with used product. For further information on applications, storage and handling contact Loxeal Technical Service.

## Safety and handling

Consult Material Safety Data Sheet before use.

## Note

The data contained herein, obtained in Loxeal laboratories, are given for information only; if specifics are required, please contact Loxeal Technical Department. Loxeal ensures abiding quality of supplied products according to its own specifics. Loxeal cannot assume responsibility for the results obtained by others which methods are not under Loxeal control. It is user's responsibility to determine suitability for user's purpose of any product mentioned herein. Loxeal disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Loxeal products. Loxeal specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.

Stos12500e/2 07/12 Pag.1/1